TRIAL: An Information Retrieval System for Creating, Maintaining, Indexing, and Retrieving from Files of Textual Information

USER'S MANUAL

1. This document has been approved for public release and sale; its distribution is unlimited.

Lorraine Borman
Donald Dillaman
Vogelback Computing Center
Northwestern University
Evanston, Illinois
October 1968
Revised December 1968
NUCC118



Reproduced by the CLEARINGHOUSE for Federal Scientific & Technical Information Springfield Va. 22151

Supported in part by the Air Force Office of Scientific Research under Grant No. AFOSR 68-1593, entitled "Man-Machine Interaction in Information Retrieval Systems". This support contributed to the completion of TRIAL for the CDC 6400 and is intended to aid the development of a remote terminal retrieval system.

TABLE OF CONTENTS

<u>P</u>	age
Program Description	1
Flow Diagram	2
Input Data Preparation	3
File Structure	3
Input Data Format	4
Levels of Information	8
	13
	14
	21
	22
	23
	24
•	25
	25
	25
	26
	26
	27
	28
	30
	31
	32
	32
· · ·	35
	40
	43
	46
References	7.0
Appendices	

LIST OF FIGURES


		Page
1.	Keypunch Instructions for TRIAL Bibliographic Applications	5
2.	Bibliographic Coding Form	6
3.	Sample Format for M-R Codebooks	. 7
48.	Sample Input Using Repeating Groups	9, 10
4b.	Search Command of Repeating Group Information	11
4c.	Output Illustrating Repeating Group Concept	. 11
5.	Sample Deck to Create a Master File from Card Input	
6.	Sample Deck to Create a Master File from Tape Input	
7.	· · · · · · · · · · · · · · · · · · ·	
8.	Sample Search Command	. 27
9.	Output from Search Command	. 29
10.	Sample Deck to Search and Retrieve Items from an Existing	
	Master File	. 31
11.	KWIC Output, Wraparound	. 33
12.	KWIC Output, using NOWRAP Feature	
13.	Title Index to Vogelback Computing Center Library - KWOC	
	Format	. 37
14.	KWOC Index by Author	. 38
15.	*AUTHOR(short-form) Index	
16.	Sample Deck to Produce Author and Title Indexes in KWOC Forms	

Program Description

TRIAL* is an information processing system that will perform editing, indexing, and retrieval of textual and certain types of numeric information. The system allows for the creation and maintenance of a master file (EDIT), indexing on words designated as "key" words ., alternatively, on every word in the text, excluding those common terms that are user supplied as a "stop" word list (INDEX), and computer retrieval and printout of entries that satisfy a user search command (SEARCH). The system is designed such that any one or any combination of the above features can be achieved through one computer run with proper control cards.

The system is sufficiently flexible to handle diverse applications in information retrieval. TRIAL has been successfully used at Northwestern for a "Selective Dissemination of Information" (SDI) system which automatically notifies social scientists of new journal articles that appear to fit their personal interests, to retrieve information from data files where the description of the study and the questions or variables used were in machine-readable form, and to select students for overseas work by retrieving from personnel files those individuals whose background satisfied the requirements of the project. The system is especially adaptable to large masses of bibliographic data where either selective bibliographies or various forms of indexes are desired.

^{*}TRIAL was originally written in machine language for the IBM 709 (1964) and rewritten for the CDC 3400 (1966) by William H. Tetzlaff of Northwestern University under the supervision of Professor Kenneth Janda of the Political Science Department. See References #9, 10, 12.



INPUT DATA PREPARATION

The TRIAL system is a series of user-oriented FORTRAN routines designed to facilitate the computer retrieval and manipulation of textual information. Design specifications have emphasized ease of use, modularity, effectiveness of retrieval, and a realistic approach to the development of a cost-conscious system.

File Structure

The TRIAL file structure allows for a maximum of nine levels of record definition within an entry; an entry is considered to be all of the information for one unit of analysis. It may be ten cards defining author, title and abstract for an entry in a bibliographic file, or 500 cards describing a FORTRAN computer program: input/output specifica+ions, error conditions, size limitations, etc. Individual applications as designated by the research design may utilize from one to all nine distinct levels of information. Any level may have new information added to it, or, if original research needs change, new levels may be added to the existing file.

The first step of file creation is definition of TRIAL structure. Each information level is defined by the user so as to meet his needs. Although the programs do not expect specific forms of input within any of the levels (with the exception of level one), it must be stressed that consistency over records in a file is of utmost importance. A standard bibliographic file might include:

Level 1: Author

Level 2: Title

Level 3: Source and date of publication

Level 4: Library call number

Level 5: Descriptors: textual or coded

Level 6: Abstract

The first three levels of information would be considered as essential before entering the file; items 4, 5, and/or 6 might be originally available and if so, would be entered as original input. Any entry, in this case, bibliographic reference,

could contain any or all of the six defined sets of information. Information within any level could be added to an entry by subsequent update of the file.

In addition, levels 7, 8, and 9 might be utilized also in the future as research needs and goals become more defined.

Input Data Format

The input format utilizes 60 characters of free-field information per line, a one character numeric identifier of the level of record definition in column 75, and nineteen characters of optional reference code. This 60-character text per line format is generally compatible with IBM KWIC, the Inter-University Consortium for Political Research codebook files, and the recommendations established by the Council for Social Science Data Archives for machine-readable codebooks. Keypunching of data begins after research needs and file definitions have been established. One method of preparing bibliographic entries is shown in Figure 1, Keypunch Instructions for TRIAL Bibliographic Applications, and Figure 2, TRIAL Bibliographic Coding Form. A file of machine-readable codebooks to survey research studies might follow the coding instructions illustrated in Figure 3, Sample Format for Machine-Readable Codebooks-Intersocietal Information Center.

Note: Input may be any alphanumeric characters. The only restriction is that a line (card) may not begin with an asterisk.

Vogelback Computing Center Library Bibliographic Coding Form Instruction Sheet for Keypunching

Author cards: Level 1

Last name, first name (or initials)

Punctuation only if desired.

For individual authors, 18 columns per entry:

Author 1 col. 1-18

Author 2 col. 21-38

Author 3 col. 41-58

Author 4 col. 1-18 card #2 of type 1

If corporate author, punch col. 1...n as needed.

Title cards: Level 2

Titles can be punched as desired, free field, col. 1-60. Use as many cards (lines) as needed.

Source cards: Level 3

Col. 1-60 free field. Punch as desired. Do not prepare copy with semi-colons.

Suggested format:

city, publisher, year.

Abstract cards: Level 5

Col. 1-60 free field. Indenting for paragraphs by starting first card in col. 3 or col. 5, or alternating, card 1, col. 1 and succeeding cards, col. 3.

Do not hyphenate words. If a word cannot be completed in col. 60, go on to a new line (card).

It is suggested that abstracts be typed using 60 characters per line so that the keypuncher can exactly follow the copy provided.

DATA CARDS MAY NOT BEGIN IN COLUMN 1 WITH AN ASTERISK.

Figure 1.
Keypunch Instructions for TRIAL Bibliographic Applications.

Vogelback Computing Center Library Bibliographic Coding Form

Lorraine Borman Northwestern University April 1968

			Level	Accession No.
Author: Type 1	Love, Patricia	Oldfather, Paula	Col.75	
Title: _ Type 2		estionnaire - Auxiliary Programs	2	
Source:_ Type 3	Rand Corporation, col. 1-60 August, 1968	Santa Monica California	3	
Descript Type 4	ors:42		4	
Abstract Type 5	::		5	

Programming by Questionnaire is a method by which many computer programs can be produced with a considerable saving of time, effort, and cost. The present Memorandum complements two others in this series by presenting five small computer programs that facilitate the application of Programming by Questionnaire in general, and provide additional analysis of the JSSPG programs.

Level Study No. Nc. STUDY 136 A COMPARATIVE ANALYSIS OF THE RELATIONSHIP 136 Title - - -THEEN SEVERE ENVIRONMENTS AND SACRED URIENTATIONS 136 136 THIS STUDY REVIEWS THE UNIFORMITIES AMONG THE SACRED 136 ORIENTATIONS OF SOCIETIES WHICH EXIST IN THE MOST SEVERE 136 Description ENVIRONMENTS ON EARTH. THE TOTAL DATA FOR EACH SUCIETY ARE 2 136 of -- -FOURTY-SIX VAPIABLES INCLUUED UNDER THE FOLLOWING TUPICS---2 136 Contents ENVIRONMENT AND RELEVANT CHARACTERISTICS. ORGANIZATIONAL 2 136 STRUCTURE, ALLOCATION OF MESOURCES, ROLE-DIFFERENTIATION, 2 136 IDEATIONAL STRUCTURE, RELIGIOUS ORIENTATION, AND RECENT 2 136 HISTORY. THERE ARE FOUNTLEN SOCIETIES WITH ONE CARU OF DATA 2 136 PER SOCIETY. 136 IN 1963, THE DATA WERE COLLECTED BY BERNARD BECK 3 136 Data collect-AND WERE SUBMITTED TO THE DEPARTMENT OF SOCIOLOGY AND 136 ion, sponsor-ANTHROPOLOGY AT PRINCE ON UNIVERSITY IN PARTIAL FULFILLMENT 136 ship, techni-OF THE REQUIRMENTS FOR THE DEGREE OF DOCTOR OF PHILOSOPHY. 3 136 cal informa-THE RESEARCH WAS SUPPUPIEU BY THE NATIONAL SCIENCE 3 136 tion, sources FOUNDATION - ALL INFORMATION WAS GAINED THROUGH LIBRARY 3 136 RESEARCH. 3 136 THERE ARE NO PLUS OR MINUS SIGNS PUNCHED IN THE DATA. 3 136 ALL ZERO-S ARE CONED TO INDICATE INSUFFICIENT EVIDENCE. 3 136 136 THE DATA HAS NEVER HEEN PUBLISHED EITHER IN TOTAL OR 136 Publications IN PART . 136 reporting-136 data IDENTIFYING INFORMATION 136 5 136 CONTAINS THE IDENTIFICATION CODE OF EACH SOCIETY L. 1-2 15 136 Information COL. 3 5 136 about data CUNTAINS THE NAME OF THE SOCIETY CORRESPONDING COL. 4-9 5 136 and units --TO THE IDENTIFICATION CODE 5 136 of analysis 01 ESKIMU 5 136 02 YUKAGH 5 136 DAN EO 136 5 114 ABH CA 136 5 05 BUSH 136 06 SHOSU 136 07 PYGHIE 136 OR NEGHLI 136 09 ALGUNK 136 10 AHH TS 136 11 AHH AL 136 15 SILINO 136 13 VEUUAS 136 14 LACANU 136 COL. 10 HLANK 136 136 PUPILLATION DENSITY (IN PERSONS PER SQUARE COL. 11 110 136 Variable € 117 136 O. INSUFFICIENT EVIDENCE 136 Response 1. 1/1 (0 1/5 118 136 Category 2. 1/h TU 1/9 118 136 3. 1/13 To 1/16 118 136 4. 1/13 TO 1/35 Card col **(De** 136 5. AS LUW A5 1/100 118 136 5. 45 LUN A5 1/250 variable 118 136

Figure 3.

Level One Information

Level one information is normally used for authors in a bibliographic file and is processed by the system in a slightly differenc method than other records. Up to three individual authors may be punched in each author card, using columns 1-18, 21-38, and 41-58. The authors last name is punched first, followed by his initials (or first name). Punctuation may be included.

A corporate author is signified by the presence of a character in either column 19 or 20. A name such as ASSOCIATION FOR COMPUTING MACHINERY would be treated as a corporate author and for certain indexing purposes would be considered as a single entity; in all other instances, i.e., keyword indexes or searching procedures, each work would be considered as an entity.

Levels Two Through Six

Information levels two through six are recorded as free field using sixty characters per line with the restriction that a word may not continue from one line to the next. Hyphenation operates to treat the hyphenated characters as one word.

Levels Seven Through Nine

Levels 7 through 9 are, for indexing purposes, handled in the same manner as praceding levels (2-6) but are considered as "repeating group" information by the search and retrieval routines. This data may be the codebook of a study on underdeveloped nations where the level 7 information would be the variable being studied, level 8 the coding categories, and level 9 source of coded information. In other applications the repeating group concept might be considered as "propositions" and "elaboration". Searching levels 7-9 would retrieve the identification levels of an entry together with only those repeating groups which satisfy the search command. Figures 4s,b,c show repeating group input (4a) and the output (4c) produced by a search (4b) of level 7 information. In this example the file to be interrogated contains information on 200 studies of a cross-national nature.

BETHERN (D A COMP.	ARATIVE AN	ALYSIS OF TH	E RELATIO	NSHIP		1 1
REIDDER '	rfvfde ex	/TDANMPLITE	ALCO METATOR	GA 15. 4.			
op. wee.v	DEACHE EM	ATMONWENTS	ALYSIS OF TH AND SACRED	CHIENIATIO	VS		1 1
							1 1
OPIENTATI	2001 RE	IEWS IME (JNIFORMITIES	AMONG THE	SACRED		2 1
ENVIDANI	IUND UP 5	CIETIES MI	ICH EXIST I	N THE MOST	SEVERE		2 1
EUINTA-E	TIME ON E	ARIN. THE	TOTAL DATA	FOR EACH S	CLETY ARE		2 1
	'87180	.P.O. 118CH UIDP	PER SECTION 1 PROPERTY 13 CT	Dist 1 :: M T AMA	TABICC		2 1:
& TRUE TURE		CCANAL CUM	444015413110	39 CHUANIZA	NTIUNAL		2 1
Theaton	LY ALLUCA	ION OF RES	GURCES, ROL	E-DIFFERENT	TATION		Ž į
IDEA I I UNA	ar structi	IRE. KELIGI	COLLECTED BE PARTMENT OF DEGREE OF DO IT WAS GAINED	TIUN, AND	ECENT		2 1:
DED CACLE	INERE AF	RE FOURTEEN	SOCIETIES	WITH ONE CA	ARD OF DATA	ı	2 13
PER SUCIE	itt: 140- Tur e						2 13
AND VEDE	Jani teot	AIA WERE	COLLECTED B	Y BERNARD 8	BECK		3 13
ANTUBODOS	SOR Y- DO) IC THE DE	PARTMENT OF	SOCIOLOGY	AND		3 13
AR THE BE	MITTING PR	INCETON UN	INERSITY IN	PARTIAL FL	ilfillment		3 13
or ing Re The neces	BOT MENTS	FOR THE O	egree of Do	CTOR OF PHI	LOSOPHY.	•	3 13
FOL REDEA	INCH WAS	UPPORTED B	Y THE NATIO	NAL SCIENCE	•		3 13
SECTABLE	ALL I	NECRMATION	WAS GAINED	THROUGH LI	BRARY		3 13
RESEARCH: THESE			.				3 13
17575 - 7500	. ARE NU P	LUS OR MIN	IIS SIGNS PU	NCHED IN TH	E DATA.		3 13
MPF SEKA	S ARE COL	EN IS INDI	CATE INSUFF	ICIENT EVID	ENCE.		3 13
THE DA	TA HAC NO	WED BES	INS SIGNS PU CATE INSUFF				3 13
INE DA	IN CATI MIL	AFH REEN D	UBLISHED EI	ther in tot	AL OR		4 13
M PAKI .	ı						4 13
			<u> </u>				4 13
	10	ENTIFYING	INFORMATIO	V			5 13
101 1-2	00074746						
OF 1-5	CONTAINS	THE IDENT	IFICATION C	DDE OF EACH	SCCIETY	-	5 13
							5 13
							5 13
	CONTAINS TO THE I	THE NAME DENTIFICAT	OF THE SOCI				5 13 5 13
	CONTAINS TO THE I	THE NAME DENTIFICAT ESKIMO					5 13 5 13 5 13
	CONTAINS TO THE I 01 02	THE NAME DENTIFICAT ESKIMO YUKAGR				ı	5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03	THE NAME DENTIFICAT ESKIMO YUKAGR ONA				ı	5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04	THE NAME DENTIFICAT ESKIMO YUKAGR ONA ABR CA				- -	5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04 05	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH				- - !	5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04 05 06	THE NAME DENTIFICAT ESKIMO YUKAGR ONA ABR CA RUSH SHOSU					5 13 5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04 05 06 07	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE				-	5 13 5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04 05 06 07 08	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT				-	5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04 05 06 07 08	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK				-	5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS				-	5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL				-	5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRINO					5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRINO VEDDAS					5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 4-9	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRINO					5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 4-9	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRINO VEDDAS					5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 4-9	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13 14 BLANK	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND	OF THE SOCI	ETY CORRESP	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 4-9	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13 14 BLANK	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRINO VEDDAS LACAND CN DENSITY		ETY CORRESP	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 4-9	CONTAINS TO THE I O1 O2 O3 O4 O5 O6 O7 O8 O9 10 11 12 13 14 BLANK POPULATI: MILE	THE NAME DENTIFICAT ESKIMO YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRINO VEDDAS LACAND CN DENSITY	OF THE SOCION CODE	ETY CORRESP	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 4-9	CONTAINS TO THE I O1 O2 O3 O4 O5 O6 O7 OR O9 10 11 12 13 14 BLANK POPULATI MILE O•	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 6 13 6 13 7 13 7 13 7 13
OL. 4-9	CONTAINS TO THE I O1 O2 O3 O4 O5 O6 O7 OR O9 10 11 12 13 14 BLANK POPULATI MILE O•	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 10	CONTAINS TO THE I O1 O2 O3 O4 O5 O6 O7 OR O9 10 11 12 13 14 BLANK POPULATI MILE O•	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 4-9	CONTAINS TO THE I O1 O2 O3 O4 O5 O6 O7 OR O9 10 11 12 13 14 BLANK POPULATI MILE O•	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 4-9	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13 14 BLANK POPULATI	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
OL. 4-9	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13 14 BLANK POPULATI	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 6 13 7 13 7 13 8 13 8 13 8 13 8 13 9 13 9 13 9 13
OL. 4-9	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13 14 BLANK POPULATI	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 6 13 6 13 7 13 7 13 8 13 8 13 8 13 8 13 8 13 8 13 8 13 8
OL. 10 OL. 11	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13 14 BLANK POPULATI	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 6 13 6 13 7 13 8 13 8 13 8 13 8 13 13 13 13 13 13 13 13 13 13 13 13 13 1
OL. 10 OL. 11	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13 14 BLANK POPULATI	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG		5 13 5 13 5 13 5 13 5 13 5 13 5 13 6 13 6 13 7 13 8 13 8 13 8 13 8 13 8 13 8 13 8 13 8
OL. 10 OL. 11	CONTAINS TO THE I 01 02 03 04 05 06 07 08 09 10 11 12 13 14 BLANK POPULATI	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE (IN PERSONS OF THE SOCION CODE	PER SQUARE	CND I NG	110 110 110 110 110 110 110 110	5 13 5 13 5 13 5 13 5 13 5 13 5 13 5 13
	CONTAINS TO THE I O1 O2 O3 O4 O5 O6 O7 OR O9 10 11 12 13 14 BLANK POPULATI MILE O. 1. 3. 4. 5. 6.	THE NAME DENTIFICAT ESKING YUKAGR CNA ABR CA RUSH SHOSU PYGMIE NEGRIT ALGONK ABR TS ABR AL SIRING VEDDAS LACAND CN DENSITY INSUFFICIER	OF THE SOCION CODE	PER SQUARE	CND I NG	110 110 110 110 110 110 110 110	5 13 5 13 5 13 5 13 5 13 5 13 5 13 6 13 6 13 7 13 8 13 8 13 8 13 8 13 8 13 8 13 8 13 8

40 A

COL.	13	POPULATION DECLINE	137	136
		O. INSUFFICIENT EVIDENCE	138	136
		1. EXTINCTION	138	136
		2. VERY GREAT DECLINE SINCE OUTSIDE CONTACT		136
-		3. SOME DECLINE	138	136
		4. NO DECLINE	138	136
		5. VARIABLE EFFECT	138	136
		•		
		•		
		ı		
		•		
				104
cor.	40	LEADERS	407	136
		1. FATHER OF FAMILY AND/OR THE EXTENDED	408 408	136 136
		FAMILY TOWNS TOWNS	408	
		2. INFORMAL AND TEMPORARY 3. HEADMAN AND SPECIFIC LEADERS FOR SPECIFIC		
		AREAS	408	
		4. OLDER MALES. AND BAND LEADERS	408	
		5. INITIATED MEN AND HEADMAN	408	
		6. MATURE MEN, AND HEADMAN	408	
		7. BAND HEADMAN	408	
		8. BAND LEADER AND EXTENDED FAMILY LEADER		
		9. CLAN HEADMAN AND COUNCIL OF CLDER MEN	408	
			408	136
COL.	41	FOREIGN RELATIONS	417	
		1. LIMITED	418	
		2. MINIMAL AND OFTEN HOSTILE	418	
		3. MINAMAL BUT GENERALLY PEACEFUL	418	
		4. AVOID INTER-GROUP CONTACT EXCEPT FOR	418	
		TRADING AND GIFT EXCHANGE	418	
		5. DEFENSIVE AGAINST INFRINGEMENT	418	
		6. SUSPICION. BUT NO HOSTILITY	418	
		7. HARMONIOUS INTER-GROUP CONTACTS WHEN BASED		
		ON KINSHIP PRINCIPLES	418 418	136 136
		9. REGULAR AND WELL-ORDERED	418	136
601	. 42	FREQUENCY OF WARFARE	427	
COL	72	1. UNKNOWN AT PRESENT	428	136
		2. VIRTUALLY UNKNOWN	428	136
		3. ONLY OCCASIONALLY	428	136
		4. UNKNOWN IN MOST AREAS	428	136
		5. FREQUENT OCCURRENCE	428	136
Įe.		6. CONSTANT, TAKES HEAVY TOLLS	428	136
			428	136

Figure 4 (a) cont. (open dotted areas indicate intervening data)

CROSS NATIONAL SEARCH FOR PROPOSITIONS,
(
(FOREIGN*RELATIONS) .OR. (DIPLOMATIC*RELATIONS) = 100,
)\$

Figure 4 (b) Search of Level 7 Information.

CROSS NATIONAL SEARCH FOR PROPOSITIONS

STUDY 136 A COMPARATIVE ANALYSIS OF THE RELATIONSHIP BETWEEN SEVERE ENVIRONMENTS AND SACRED ORIENTATIONS

THIS STUDY REVIEWS THE UNIFORMITIES AMONG THE SACRED CRIENTATIONS OF SOCIETIES WHICH EXIST IN THE MOST SEVERE ENVIRONMENTS ON EARTH. THE TOTAL DATA FOR EACH SOCIETY ARE FOURTY-SIX VARIABLES INCLUDED UNDER THE FOLLOWING TOPICS--- ENVIRONMENT AND RELEVANT CHARACTERISTICS. ORGANIZATIONAL STRUCTURE, ALLOCATION OF RESOURCES, ROLE-DIFFERENTIATION. IDEATIONAL STRUCTURE, RELIGIOUS ORIENTATION, AND RECENT HISTORY. THERE ARE FOURTEEN SOCIETIES WITH ONE CARD OF DATA PER SOCIETY.

4 44 44 (186	COL. 41 FOREIGN RELATIONS
Printout of only that	1. LIMITED
repeating group that satisfied the search	2. MINIMAL AND OFTEN HOSTILE 3. MINAMAL BUT GENERALLY PEACEFUL 4. AVOID INTER-GROUP CONTACT EXCEPT FOR
command.	TRADING AND GIFT EXCHANGE 5. DEFENSIVE AGAINST INFRINGEMENT 6. SUSPICION. BUT NO HOSTILITY
	7. HARMONIOUS INTER-GROUP CONTACTS WHEN BASED ON KINSHIP PRINCIPLES 9. REGULAR AND WELL-ORDERED

PHRASES....
FOREIGN

RELATIONS

The user might want to retrieve only those studies containing variables on "gross national product in Nigeria." A level 7 search of the file would retrieve and print only the names of those studies in the file containing data on Nigeria and GNP, their location in the data file, and the coding procedure used, i.e., in dollars, in pounds, etc. Since the user is not interested in other variables that might be part of the study, the use of the repeating group search enables him to obtain a quick response to his search command but one which satisfies his needs. Another individual might be interested in variable construction; he would want a printout of a total codebook and would, therefore, use a generic search command, possibly the name of a known study, so as to retrieve an entry in its entirety. A level 7 search, however, is used to retrieve specific selections of information from the body of entry.

TRIAL PROCESSING: CREATING A MASTER FILE

TRIAL consists of six programs within an "overlay"* structure: TRIAL, EDIT, SEARCH, INDEX, SORTER and PRINT. TRIAL serves as the Executive, issuing calls to the other programs as needed. Processing of new input data is the function of the EDIT routines.

In many research situations where large amounts of data are involved, it is usually necessary to place all of this information on a "master file" tape for subsequent processing. The EDIT program consists of ten routines which generate this file.

The EDIT programs analyze instruction cards and set appropriate switches. New input to EDIT is internally reformatted for speed in processing and for ease of update by subroutine CREATE. A header word is generated for each entry containing (1) a reference code as user specified, (2) the date of entry into the file, (3) a serial number for updating, and (4) each line of an entry is numbered by tens for subsequent alteration within an entry. Each record is handled individually with information levels one through six analyzed before any of the repeating group levels are scanned. The WRITEMS, PUT and PUT1 routines write the master file and all other files as specified by the user instructions. Output records consist of 504 words per block. Error checking of new and update input is performed according to user option. (These functions are currently being revised; a memo will be distributed to TRIAL users at the time of completion.)

Many circumstances require frequent changes or additions to the master file as errors are detected or as new information is collected. The procedures connected with this task are known as updating the master file. The

^{*}overlay: The technique of repeatedly using the same blocks of internal storage during different stages of a problem, e.g., when one routine is no longer needed in internal storage, another routine can replace all or part of that storage. The overlay concept thus permits the breaking of a large program into segments which can be used as required to implement problem solution.

TRIAL system allows for the deletion of entries within a file (DELETE), replacement of one entry by one or more entries (REPLACE), insertion of entries after a given entry (AFTER), and alteration within an existing entry (ALTER). Any number of update commands are acceptable with one call to the EDIT program.

All of these update commands allow the user to modify the existing master file and process either indexing and/or searching instructions in one computer run.

All update processes are performed sequentially. Although the use of disk files allows updating on a scratch file with the updated file rewritten on the original master, good programming practice, for obvious reasons, does not recommend this type of usage. Especially in the case of large tiles, where original information may not be readily accessible, the use of input and output magnetic tape files is recommended. The EDIT master file can be processed immediately as part of the original job or, if written on a magnetic tape, can be saved for future processing.

EDIT Control Cards

*EDIT

This card calls in the various editing routines and signifies that new data or update information are to be inputted to a master file.

Instruction Card

Various files may be assigned at the option of the user. In addition, he may also request options which will 1) produce listings of the input data (LIST), 2) specify the type of reference code to be generated for the file (REFERENCE CODE TYPE = i), and

3) instruct the system to only process additions to an existing file (ADDITIONS = u).

Instruction Card (cont'd.)

All instructions are typed in free-field format separated by a comma. The last command must be followed by a period. All words enclosed within brackets below are optional.

NEW MASTER . u, (required)

This is a file assignment for the unit number of the master file to be created. If TRIAL is being operated in a disk file system environment, u may be assigned to any file accessible to user programs. Files 1 through 5 are available at Northwestern University.

OLD MASTER = . (optional)

This command assumes that a magnetic tape file has previously been generated and is to be updated during this computer run. u would equal the logical unit number of the tape drive to be assigned to the existing master tape.

ALTERNATE Input = u, (optional)

The use of the INPUT file assignment assumes that data is to be inputted to the system from a magnetic tape rather than cards.

LIST = u, (optional)

The LIST command instructs the EDIT routines to write a file containing a formatted listing of the marter file that can be printed off-line. u may equal a logical number of a tape to be assigned or may be equated to the normal output unit; at Vogelback this would

Instruction Card (cont'd.) NO MAP, (optional)

[JUST]ADDITIONS = u,

REFERENCE CODE TYPE - 1,

A MAP of the master file is automatically generated by the EDIT routines. The MAP indicates the user defined reference code and the internal sequence number assigned by TRIAL to each entry together with the date the entry was added to the master file. The MAP serial number <u>must</u> be referenced if update capabilities are to be utilized. MAP is automatically printed as part of the output file if not specified.

In many instances a user desires to search or index only additions that have been entered onto the master file. The ADDITIONS command instructs the program to write new entries onto file "u" for subsequent processing. It should be noted that the muster file generated will contain all entries. This file assignment is extremely valuable when working with massive amounts of data or in the intermediary stages of file building.

Reference codes, such as Defense Documentation Center numbers, or accession numbers, are user defined and may or may not be present in an entry. All reference codes are constructed from the first line of level 1 information of an item. It is suggested, however, that when constructing a large file, a serial number should be included on every card of an entry.

REFERENCE CODE TYPE = 1, (cont'd.)

These code fields may, upon option, be used for indexing and/or search and retrieval.

TRIAL recognizes and processes five types of reference codes:

i = 1 columns 61-72, 76-80

i = 2 columns 1-10, 61-67

i = 3 columns 1-5, 61-67, 76-80

i = 4 columns 61-67, 1-5, 76-80

i = 5 columns 76-80

If the REFERENCE CODE command is not specified, type 1 code is assumed. An example of the Instruction card to create a master file, reading data from a magnetic tape, and containing a serial number in columns 76-80 to be used as a reference code would be:

NEW MASTER = 1, INPUT = 3, REFERENCE = 5.

Logical units 1 and 3 would be assigned to the physical tapes using local installation system controls.

*DATA (required)

The DATA command signifies the beginning of data to be edited. Instructions for EDIT such as INSERT and the update commands are considered, in this context, to be "data".

Instruction Commands

* INSERT, ENTRY = x, INCREMENT = y.

The INSERT command instructs the EDIT routines to "insert" all entries following the command card onto the master file. It is mandatory when creating a new master file. x is the initial value of the serial number to be

Instruction Commands (cont'd.)

generated by EDIT. Unless specified, it is set at 10. y is the value that the internal serial number will be incremented by for each successive entry. If not specified, increment is set at 10. If a file of 50 entries was to be generated, using *INSERT., their MAP would read:

entry 1 0010

entry 2 00020

entry 50 00500

Stepping of the increment value by 10 is especially useful when the possible need to insert entries into specific areas of the master file might arise. One example of this use would be in maintaining alphabetical order within the file. Original input entries could be incremented by tens, or even by 100's. If INCREMENT = 10, 9 additional entries could later be placed between two existing entries. If INCREMENT = 100, 99 additions could be added between two existing records.

To update an existing file

For all update commands, the value of n is the serial number of the entry to be referenced as indicated on the MAP of the existing master file. *DELETE, ENTRY = n.

This command causes the deletion of the entry that has the serial number matching the number specified.

*REPLACE, ENTRY = n.

REPLACE is used when an existing entry is to

*AFTER, ENTRY = n.

be deleted and replaced by one or more entries. AFTER is used to write m entries after the nth entry specified. If the user desired to maintain an alphabetical order on the file he would use the AFTER command. AFTER is also used to place additional entries after the last record that had been on the old master file.

*ALTER, ENTRY = n.

ALTER allows the user to correct or add information to a record on t e file. The data cards to be used in an ALTER operation are punched in TRIAL internal record format See Appendix 1.

*INSERT ENTRY = n, INCREMENT = n. INSERT indicates that new data is to be written on the master file as the beginning records. These entries will then be followed by the records that were on the old master file. If the old file had been incremented 10 to 500, entry and increment n should be set at 1 to allow for 9 new insertions to be written without upsetting the sequential ordering of the file. INSERT may also be used in cases to insert a new r cord or

*INSERT, ENTRY = n, INCREMENT = n. records but it must follow either a DELETE, (cont'd.)

REPLACE, ALTER, or AFTER function.

*OUTPUT

To list the master tape. The *OUTPUT option allows the user to print the master file at any time subsequent to an EDIT operation. This is primarily to obtain a listing when the LIST option was not used during the EDIT run. If multiple copies are desired, the LIST = n option on the instruction card must be used (see p.15).

*SEQUENCE, ENTRY = n, INCREMENT = n.

The *SEQUENCE command is used when a resequencing of the master file is desired. This is especially helpful when many updates have been performed, possibly using different sequencing methods. (See pp 17-18 for discussion of ENTRY and INCREMENT options). If E and I are not specified, entry will begin at 10 and be incremented by 10's.

*END

END signifies the end of the edit process.

For those jobs where either the initial amount of input data is small or where it is assumed that there will be no need to revise or alter the original data, or in a situation which requires only one pass of the data through the program, the FDIT processes need not be of concern to the user. This one-time job can be stope illustrated by the following example:

A research report discussing advances in the information sciences and including a survey of the existing literature has been written which must include a bibliography of cited references in alphabetical order. Input to TRIAL would consist of the following:

```
(Local installation system cards)
     *EDIT
     NEW MASTER = 1.
     *DATA
     *INSERT.
                 BECKER J HAYES D
                 Information Retrieval
entry 1
                 Wiley and Sons, 1964.
entry 2
entry n
     *END
     *INDEX
     *WORDS, AUTHOR, CARDS (1), NULL.
     *KWCC, AUTHOR, CARDS (1, 2, 3).
     *END
     *PRINT
     SINGLE COLUMN, CARDS (2, 3).
     *END
```

Printout of this job would be photo-ready copy that is amenable to any offset process, or, if only one copy is required of the report, could be inserted directly into the document. By writing the master file to a magnetic tape, this bibliography could be subsequently interrogated.

TO CREATE A MASTER FILE FROM CARD INPUT AND SAVE IT ON MAGNETIC TAPE FOR FUTURE PROCESSING:

VCC System Cards	VLORR, CH1235-9999, CM66000, T1000.
	REQUEST(TAPE1) HANG TAPE XXXX (user-supplied tape)
	LIBRARY(TRIAL) (Check Library Directory on Center bulletin board for
	MAP, OFF. name of current version.)
	LGO. Tape numbers 1 through 4 may be used. Note that
	7-8-9 End of Record the number used on the REQUEST card must match
TRIAL System Cards:	number used on control card.
Required	*EDIT
Control Card (various options) See pp. 14, 15, 16, 17	NEW MASTER = 1.
Required	*DATA
Instruction Card (various options) See p. 17	*INSERT.
	Data Cards
Required	*END

6-7-8-9 End of Information

Figure 5. Sample Job Deck Structure

TO <u>CREATE A MASTER FILE ON TAPE</u> FROM DATA PREVIOUSLY WRITTEN ON MAGNETIC TAPE
IN TRIAL TAPE INPUT FORMAT (UNBLOCKED, 80 CHARACTER RECORD FORMAT, WITH EOF
AT END OF REEL):

VCC System Cards VLORR, CH.....

REQUEST(TAPE1) HANG XXXX (master file will be written on this tape)

REQUEST(TAPE2) HANG XXYY (input data tape)

LIBRARY(TRIAL)

LGO.

7-8-9 End of Record

TRIAL System Cards:

*EDIT

NEW MASTER = 1, INPUT = 2.

*DATA

*INSERT.

*END

6-7-8-9 End of Information

TO UPDATE AN EXISTING MASTER FILE AND PRINT A LISTING OF THE UPDATED MASTER FILE:

VCC System Cards VLORR, CH.....

REQUEST(TAPE1) HANG XXXX (existing OLD master file)

REQUEST(TAPE2) HANG XXYY (write updated master (NEW) on this tape)

LIBRARY(TRIAL)

LGO.

7-8-9 End of Record

TRIAL System Cards:

Required *EDIT

See pp. 15, 16, 17, 18. . . . OLD MASTER = 1, NEW MASTER = 2, LIST = 61.

See p. 19. *DELETE, ENTRY=103.

See p. 19. *REPLACE, ENTRY=117.

Data cards for entry which replaces #117

Items to be added to file; will be written after last entry (#200) of old master file

Required *END

6-7-8-9 End of Information

Search and Retrieval Methods

Retrieval of information can be obtained by two distinct methods: 1) the use of a search command which establishes specific criteria for item retrieval or 2) indexed output of a KWIC or KWOC type format which generally is then used for manual, or desk, retrieval. In Section A discussion will be limited to the first method, the use of English words and operators to establish search criteria and print the retrieval entries. Section B will describe the indexing and print routines.

A. SEARCH

Any master file created by the EDIT program can be searched. The important features of the SEARCH program are 1) its ability to search textual material for specified words or combinations of related keywords, and 2) its use of the Boolean operators, AND, OR, and NOT, giving the user the ability to specify how these words must appear in combination with each other. If he does not retrieve relevant documents, he can rephrase his command, in much the same manner as the user of a library card catalog. Retrieval from a TRIAL search can be of two forms: a "short form" to allow quick scanning of title and author, or a listing of complete information contained within the entry. In the case of bibliographic files, abstracts, extracts, critical reviews, or even full text may be printed.

The Search Command

A search command is punched on control cards which are read by the Trial system. This command instructs the computer 1) what identifying information is to be printed as a "heading" at the top of each output page, 2) what levels of information of cards are to be searched, and 3) what keywords and logical relations among keywords will satisfy the search. A word is defined as an uninterrupted sequence of 20 or fewer word-forming characters: the letters

A through Z and the digits 0 through 9. Blanks and all other characters are non word-forming characters. (NOTE: The INDEX routines treat a hyphen as word-forming.)

The program considers as a phrase an, sequence of words (on records of the same level). Phrases may continue across any type of punctuation characters. Hyphenated words must be searched as if they were phrases, for example, "wordforming" would be searched for as "WORD*FORMING". Because digits 0 through 9 are defined as word-forming characters, particular numbers may be searched for as keywords.

Title Card

A card containing a title or identification label is punched by the user.

All instruction cards in SEARCH are virtually free of format restrictions, and this label might begin anywhere on the card and continue for a maximum of 60 characters. The program considers the identification label terminated when it encounters a comms which serves not only to end the identification label but also to instruct the program to look for the levels of information to be searched.

What to Search

Searches can be made on any level of information designated in the search command. Numbers representing the levels to be searched are punched after the commant that terminates the heading. These numbers may be punched in any order, and are separated by commant to improve readability. The level designation is terminated by the first left parenthesis enclosing the keyword portion of the search command.

If only levels 7, 8, or 9 (repeating groups) are designated, the search will be conducted only within records of those levels. If, however, other levels are specified, the computer will search across all specified categories.

Output from a search of repeating group levels will print all level 1-5 information plus only the repeating groups that satisfied the search command(see pp.8-12).

After reading the code number or numbers of the levels to be searched, the machine senses that it is receiving a search command when it reads a left parenthesis. Because any given command may contain more than one combination of keywords arranged in "nests" of parentheses, the program continues to read until the number of right parentheses read equals the number of left ones. It will then evaluate the logic of the command, working outward from the innermost set of parentheses.

Use of Boolean Operators

The power of the search command lies in the use of stardard logical operators expressed on the punchcard as follows: ".NOT.," ".OR.," and ".AND.". Perhaps the use of the operators can best be conveyed by constructing a sample command for the elites and decision making search. Figure 8 shows the command punched on cards.

TEST NO 1A - IIC STUDY CODEBOOKS, 7,8, (ELITE .OR. ELITES .OR. LEADERS .OR. LEADERSHIP .OR. DECISION*MAKING .OR. DECISION*MAKERS = 100.)\$

Figure 8.

This command instructs the program to select only those statements containing both one or more keywords specified within the first nest of parentheses and one or more keywords specified within the second nest. If SEARCH finds any statement of a proposition or finding which satisfies this logical combination of keywords, it will print out the statement and its supporting elaboration after printing the citation of the article and a summary of the study. A portion of the computer output produced in response to the above command is reproduced in Figure 9. The dollar sign after the last right parenthesis on the punchcards in Figure 8 indicates the end of information for a single search instruction. Many different searches can be made during one run on the computer.

Weighting of Search Terms

In addition to retrieving items according to logical combinations of keywords, the SEARCH program provides for "weighting" keywords so that retrieval occurs only if the sum of the weighted keywords in a given entry equals or exceeds a previously stated value. This value, or "hit value", is set presently at 100 (see Figure 8). Retrieval of an item is caused, therefore, when encountering one keyword weighted "100", two keywords weighted "50" each, and so on.

TEST NO 1A - IIC STUDY CODEBOOKS

STUDY 500 FIVE NATION STUDY - UNITED KINGDOM, NECK 2

ALMOND - VERBA

NORC 427 JUNE - JULY, 1959 DECK 02 N=1295 UNITED KINGDOM

53.A. WE ARE ALSO INTERESTED IN HOW WELL KNOWN THE NATIONAL LEADERS OF THE VARIOUS POLITICAL PARTIES ARE IN THIS COUN-TRY. COULD YOU NAME THREE LEADERS OF THE CONSERVATIVE PARTY. (IF ACCESSARY. TAKE DOWN THE NAMES GIVEN AND CHECK ACCURACY AFTER THE INTERVIEW. MARK THE NUMBER CORRECT FOR EACH PARTY. THEN TALLY TOTAL NUMBER CORRECT AT END OF GUESTION.)

COULD YOU NAME THREE LEADERS OF THE LABOUR PARTY. 53.8. AND CCULD YOU NAME A LEADER OF THE LIBERAL PARTY. 53.C. TALLY (CODE TOTAL CORRECT)

495. SEVEN CORRECT

1036. SIX CORRECT

1347. FIVE CORRECT

1309. FOUR CORRECT

1179. THREE CORRECT

1250. TWO CORRECT

110-ONE CORRECT

45. HERE IS A LIST OF THINGS THAT CHILDREN MAY BE TAUGHT IN SCHOOL. (HAND LIST 10) WHICH WAS STRESSED THE MOST IN YOUR SCHOOL.

RIT. HAVE FAITH IN LEADERS

.8SE. OBEY THE LAW

369. HOW THE GOVERNMENT IS HUN

2840. LOVE YOUR COUNTRY

35-. OTHER

THE FOLLOWING WORDS WERE FOUND IN THE ENTRY

MORDS

FREQUENCY

(This caused retrieval) LEADERS

Figure 9. Partial output produced from search command shown in Figure 6. The file searched contained 105 codebooks to social science studies; 39 were retrieved.

SKARCH Control Cards

*MASTER = n (optional - depending upon type of use)

*SEARCH (required)

Search command: (required)

*E3D (required)

This instruction is used only when an existing (previously created and saved) file of information is to be used as input to the search routine. n may be any unit from 1 to 5 and must be referenced on a system REQUEST card. To call in the search overlay. Free-field; title, maximum 59 characters; comma; numeric punches indicating levels of information to be searched, separated by andending with a comma; left parenthesis; search words, phrases, and operators; weight, right parenthesis; \$ to indicate end of command. (See Figure 8, page 27) To return control to executive overlay.

TO SEARCH AND RETRIEVE ITEMS FROM AN EXISTING MASTER FILE:

VCC System Cards VLORR, CH..... REQUEST(TAPE4) HANG 2044 VCC EDIT MASTER LIBRARY (TRIAL) LGO. 7-8-9 End of Record TRIAL System Cards: Required *MASTER = 4. Required *SEARCH Title Card (See SEARCH VCC BIBLIOGRAPHY FILE, 2,5, (pages 26,27) (NATURAL .AND. LANGUAGE) .OR. Search Command (See pp. 25-28) NATURAL*LANGUAGE .OR. TEXT*RETRIEVAL .OR. TEXT .AND. (SEARCH .OR. SEARCHES .OR: SEARCHING .OR. RETRIEVAL) = 10C,)\$ Required *END 6-7-8-9 End of Information

Figure 10. Sample Job Deck Structure

-31.

B. INDEX

Keyword indexing by computer is an automatic method for generating alphabetized listings of keywords contained in input material. The INDEX overlay of the TRIAL system contains 14 routines for generating keyword indexes. Input to INDEX is any file that has been created by the EDIT program, either in the same or a previous computer run.

The two most common types of keyword indexing are known as KWIC (Keyword-in-context), and KWOC (Keyword out of context). In KWIC indexing, the computer arranges selected keywords in an alphabetized column surrounded by a few words (maximum length of line=100) of the context in which the keywords occur. In KWOC indexing the selected keywords are printed in a separate column alongside the original context.

Political Science. The keywords are arranged in alphabetical order to the immediate right of the blank column. The index would be used by scanning down the vertical column of keywords to locate those of special interest. Words on the same line surrounding the keyword contain the context in which it is used. The output page width provides room for 100 characters-spaces to be printed on one line. A title* with no more than 100 characters and spaces prints out in full, although a portion of the title may be "wrapped around" and printed before or after the keyword, depending on the position of the keyword. The "wrap" feature may be eliminated by use of the NOWRAP command (see page 41). This is illustrated in Figure 12. It should be noted that NOWRAP does not print context occurring before the keyword.

^{*}The current version (4) of the KWIC routine automatically prints 18 characters of the author's name (level 1) together with title information (level 2) as one line of output.

	AKT TONOS.	-	MOM
	-	AUTHOR NAME	- YEAR
THE	BA COMMITTEE		49-4-80
BHL NO	BUSES OF PO	SPIES OF SERVICE	01-14-17
POLITICAL A	C. AND THE PROBLEM OF STATES OF STAT		9
RTY	# 2 IS	FPSTEIN LO	01-N-57
IAL		~	S-M-
CHAMACTERISTICS AND LEGISLATIVE OVERSIGHT OF		ALBHY OF	9
S (PUBLIC	ISTRATION.RUREAUCRACY). H	ROYUE EE	04-A-60
Ų.	OF POLITICAL STYLES BY	SCARRITT U	10-F-66
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	CODE FOR INVESTIGATING COMMITTEES.	MECHIC EL	/G-N-10
S GENEVA CONFERENCE OF EXPERTS (TECHNICAL DES ATTORS B	UVISORS). * S	STRICKLA D	08-X-64 64-14-164
A CREATER ON THE	EFFA [N DERSONAL A DICE AN EXECUTAR A FROM	STATE OF STA	Q . Q .
CAL	PFILIATION AND THAGERY ACKISS TA		06-A-62
	- ASIAN WOKLO.	CAHL 19	40-N-E0
THE A	OR IN THE 1958 CONGRESSIONA	WALKER	04-F-60
POLICY MAKING BY GOVERNMENT A	(PUBLIC ADMINISTRATION, BUREAUCHACY) . =	HOYER WE	04-4-40
_	IONS SUBCOMMITT	Z	
SE,	ELEMEN CUSTICES OF LEGISLATORS.		10-F-56
ANYONA LICA ANG THE LARGE MANYONDRALIAN PLOCATION (AGE	AGRICULIURE) . B THE COMMODITY CHEDIT C	O SEVENTE O)
_	40000000000000000000000000000000000000		217
- 2	DO ONOTIFICATION OF THE PROPERTY OF THE PROPER	DONES CO	
	IO TO INCIPANTURAL INTEREST		
	CAGT NA TERM	22121	2
AUSTWALIAN POLITICS AND CONSTITUTION			• N
ORY	IVIL SER		2-7-5
LECTOHAL COLLEGE REFORM CONSTITUTIONAL	I. PHESIDENTIAL ELECTION) . HUBERT	_	2-F-5
~ z	T TUG	ANDERS	ž
Z (Z SULL	2 - X - D
- ;	COLITICAL BEMAVION.		V - 2
E PUBLIC INTEREST IN JUDICIAL DECISION-MAKING AME	NATIONAL CITTURE CANAN FOLITICAL LATINGUA OF TAMERA	SCHUBERT G	02-11-54
ANO	POLITICS A CLARIFIED VIEW.	SCHLESIN	01-M-57
IMAGE OF THE	PRESIC		
SOCIALIZATION OF	STATE LEGISLATORS.	EULAU *	
H	MEHICAN TRACITION (THEORY)	ININGS	01-8-57
NEW ONE PLACE TO THE CAR MODERNE	MEXICAN CONTONISM (SEIOLER M	9-Y-
DOT CONTUR V	0. TROUGHT) 3.4100		
ASOKA IN	NOTAN POLITE	RINSKI	
HIL	ION IN AMPRICAN CITIES.	T.R.	08-N-64
Figure 1 1. KWIC computer output: sample keyword listing from the cumulative	lative		•
INDEX TO THE MIDWEST JOBTHAI OF PURITIES SCIENCE,			

FORTRAN AND ALGOL BEAR TO THE PERFORMANCE OF ARITHMETIC. #409 FORTRAN AND ALGOL SERVE ARITHMETIC. #411 FORTRAN IN FORTHE SAN HERTZ H J PROGRAMS OF SUCH PRECOMPILERS TO GENERATE SPECIAL PURPOSE PROGRAMS OF FORTRAN IV IN A FORM COMPATED UNDER THE COMPATENCE WARIATIONS INPUT AND OUTPUT EXAMPLES: AND SUBSCRIP FORTRAN IV IN A FORM COMPATABLE WITH THE COL SAOO SYSTEM CURRENTLY INSTALLED AT NORTHMESTE SPECIAL COMPUTER WHICH COMPUTES THO AND THREE-STAGE LEAST SQUA OFF FORTRAN PROGRAMMING AND COMPUTING #5 GOLDEN JAMES TO FORTRAN PROGRAMMING #5 AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLA 567 FORTRAN PROGRAMMING #5 AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLA 567 FORTRAN PROGRAMMING #5 AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLA 567 FORTRAN PROGRAMMING #5 AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLA 567 FORTRAN PROGRAMMING #5 AND ONLY A LIMITED SET OF ##PRIMITIVE## MACHINE LANGUAGE SUBROUT 769 FORTRAN PROGRAMMING #5 AND ONLY A LIMITED SET OF ##PRIMITIVE## MACHINE LANGUAGE SUBROUT 769 FORTRAN PROGRAMMING ON ONLY A LIMITED SET OF ##PRIMITIVE## MACHINE LANGUAGE SUBROUT 769 FORTRAN PROGRAMMING ON ONLY A LIMITED SET OF ##PRIMITIVE## MACHINE LANGUAGE SUBROUT 769	TON		FOR	KOZ	FOR	TOP	FOR	C	FOR		2) (9 7 2 0 0 0	9 / 2 / 3 / 5 /		705	70	FO	TOR	FOR
AND ALGOL BEAR TO THE PERFORMANCE OF ARITHMETIC, THAT IS, A USER ORIENTED SYMBOL M AND ALGOL SERVE ARITHMETIC. =. AND ALGOL USE THE FORMULA TO EXPRESS IN A SINGLE LINGUISTIC STRUCTURE AN ARBITRARI ASSIGNMENT-STATEMENT ABILITY IS COUPLED WITH ASSIGNMENTS ARE A SUBSET. WHEN THIS ASSIGNMENT-STATEMENT ABILITY IS COUPLED WITH BY PRECOMPILERS. =A WERTZ H J PROGRAM-WRITING PROGRAMS. EXTENDING COMPUTER PROGRAMS FOR INFORMATION RETRIEVAL (VINSONHALER), AND ANOTHER ANNOUNCEMEN IN FOR THE ISPUT OF SUCH PRECOMPILERS TO GENERATE SPECIAL-PURPOSE PROGRAMS OF THE COLD FEATURES AS MIXED MODE EXPRESSIONS. EXAMPLES, AND SOME POINT HAS BEEN IMPLEMENTED UNDER THE COLD SAGNIFOR COMPILER SYSTEM (CCS), A GROUP OF IV PROGRAMMING AND COMPUTER THE COLD SAGNIFORMENTLY INSTALLED AT NORTHWESTE IV PROGRAMMING AND COMPUTER WHICH COMPUTES TWO-AND THREE-STAGE LEAST SQUAIV PROGRAMMING AND COMPUTER THE COLD JAMES TO LANGUAGE. BUTH EDGE-DETECTION AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLAPROGRAMMING. = GOLDEN JAMES TO PROGRAMMING. = HARVILL JOHN B BASIC PROGRAMMING. = HARVILL JOHN B BASIC PROGRAMS DEPENDING ON ONLY A LIMITED SET OF ##PRIMITIVE## MACHINE LANGUAGE SUBROUT SYNTAX ANALYSIS. =-	TRAN	T T X	TRAN	TRAN	TRAN	TRAN	TRAN	TRAN	777	7777	7,77			TRAN		ておきる	TRAN	TRAN	TRAN	TRAN
GOL BEAR TO THE PERFORMANCE OF ARITHMETIC. THAT IS, A USER ORIENTED SYMBOL MOOL SERVE ARITHMETIC. TO EXPRESS IN A SINGLE LINGUISTIC STRUCTURE AN ARBITRARI MENTS ARE A SUBSET. WHEN THIS ASSIGNMENT-STATEMENT ABILITY IS COUPLED WITH COMPILERS. THE FORMULA TO EXPRESS IN A SINGLE LINGUISTIC STRUCTURE AN ARBITRARI MENTS ARE A SUBSET. WHEN THIS ASSIGNMENT-STATEMENT ABILITY IS COUPLED WITH COMPILERS TO GENERATE SPECIAL PURPOSE PROGRAMS OF THE IBM 1620. THE IMPORTATION OF SUCH PROGRAMS OF THE IBM 1620. THE IMPORTATIONS INPUT AND OUTPUT EXAMPLES AND SOME POTALNS SUCH EXTENDED FEATURES AS MIXED MODE EXPRESSIONS. GENERALIZED SUBSCRIP BEAN FOR THE COLOREA FOR THE CONFUTER WHICH COMPUTER SYSTEM (CCS). A GROUP OF A FORM COMPUTER WITH THE COLORAGE SYSTEM CURRENTLY INSTALLED AT NORTHWESTE GRAMMING AND COMPUTER WHICH COMPUTES TWO-AND THREE—STAGE LEAST SQUA BEASIC BOTH EDGE-DETECTION AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLASS AND SOME POTAL COMPUTER WILL JOHN B BASIC BOTH EDGE-DETECTION AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLASS ANALYSIS. THE COLORAGE SUBROUT OF SAPRIMITIVES MACHINE LANGUAGE SUBROUT ANALYSIS.	NAS	0 TO	PRO	PRO	_	14	1	1.1		· *	<		40		•	_	_;	ANO	AND	
EAR TO THE PERFORMANCE OF ARITHMETIC. THAT IS, A USER ORIENTED SYMBOL MERVE ARITHMETIC. =. ERVE ARITHMETIC. =. ERVE ARITHMETIC. =. ENVEY ARITHMETIC STRUCTURE AN ARBITRARI FORMULA TO EXPRESS IN A SINGLE LINGUISTIC STRUCTURE AN ARBITRARI FOR INFORMATION RETRIEVAL (VINSONHALER). AND ANOTHER ANNOUNCEMENT OF AND THE COLUMN RETRIEVAL (VINSONHALER). AND ANOTHER ANNOUNCEMENT OF AND THE COLUMN RETRIEVAL (VINSONHALER). AND ANOTHER ANNOUNCEMENT OF AND SOME POLICY AND THE COLUMN RETRIEVAL COMPILER SYSTEM (CCS). A GROUP OF AN COMPATABLE WITH THE COLUMN SYSTEM CURRENTLY INSTALLED AT NORTHWESTER FOR THE COLUMN SHARE. INC ENAMUAL =. ENAMUAL =.	TAX /	OXAI	GRAM	BRAN	BUAG	REFE	ROG	PROG		•	-				X X	PREC	1981	ALO	2	
AR TO THE PERFORMANCE OF ARITHMETIC. THAT IS, A USER ORIENTED SYMBOL MERVE ARITHMETIC. =. RVE ARITHMETIC. =. RYE ARITHMETIC. =. RYE ARITHMETIC. =. RYEN THE SASSIGNMENT-STATEMENT ABILITY IS COUPLED WITH PROBLET. IN PROGRAMS TO GENERATE SPECIAL-PURPOSE PROGRAMS COUPLED WITH PROGRAMS TO GENERATE SPECIAL-PURPOSE PROGRAMS COUPLENT OF SUCH PRECOMPILERS TO GENERATE SPECIAL-PURPOSE PROGRAMS COUPLENT OF SUCH PROBLEMENT AND COUPLER AND SUCH EXTENDED FEATURES AS MIXED MODE EXPRESSIONS, GENERALIZED SUBSCRIP INPLEMENTED UNDER THE CONVERSATIONAL COMPILER SYSTEM (CCS). A GROUP OF COMPATABLE WITH THE CDC 3400 SYSTEM CURRENTLY INSTALLED AT NORTHWESTE OR THE CDC 6400 COMPUTER WHICH COMPUTES TWO-AND THREE-STAGE LEAST SQUA MANUAL =. COM-SHARE, INC MANUAL =. COM-SHARE, INC BASIC BASIC RYE WP INTRODUCTION TO INTRODUCTION T	ANAC	7 X X X X X X X X X X X X X X X X X X X	HING	FOR	•	RENC	RAME	7	FOX	DEEN.	20		T 7 1			016 M				•
ARITHMETIC. ** ARITHMETIC. **	7515	7 8	*	マボド	807		7		CO	I TIP	SUCI				F C 71	MAS	À	SE TI	ERVE	EAR
TIC. =. TIC. =. TIC. =. TIC. =. TIC. =. TATIS ASSIGNMENT-STATEMENT ABILITY IS COUPLED WITH WERTZ H J PROGRAM-WRITING PROGRAMS, EXTENDING OF SUCH PRECOMPILERS TO GENERATE SPECIAL-PURPOSE PROGRAMS ONFORMATION RETRIEVAL (VINSONHALER), AND ANOTHER ANNOUNCEMEN WO MODEL VARIATIONS, INPUT AND OUTPUT EXAMPLES, AND SOME POUNDER THE CONVERSATIONAL COMPILER SYSTEM (CCS), A GROUP OF WITH THE COC JACO SYSTEM CURRENTLY INSTALLED AT NORTHWESTE AND COMPUTER WHICH COMPUTES TWO-AND THREE-STAGE LEAST SQUAUTING. = . COM-SHARE, INC ETECTION AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLAUS. THE COUPLED WITH CLAUS.	_ 8	•	•	000	+ RDG	CAC.	ONO		PATA			900			717	•	>	Ā	AR	Ö
CE OF ARITHMETIC. THAT IS. A USER ORIENTED SYMBOL M PRESS IN A SINGLE LINGUISTIC STRUCTURE AN ARBITRARI THIS ASSIGNMENT-STATEMENT ABILITY IS COUPLED WITH DROCKERS TO GENERATE SPECIAL-PURPOSE PROGRAMS O ON RETRIEVAL (VINSONHALER). AND ANOTHER ANNOUNCEMEN VARIATIONS. INPUT AND OUTPUT EXAMPLES. AND SOME PO RES AS MIXED MODE EXPRESSIONS. GENERALIZED SUBSCRIP HE CONVERSATIONAL COMPILER SYSTEM (CCS). A GROUP OF E COC 3400 SYSTEM CURRENTLY INSTALLED AT NORTHWESTE PUTER WHICH COMPUTES TWO-AND THREE-STAGE LEAST SQUA AS. GOLDEN JAMES T HARE. INC AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLA INTRODUCTION TO INTRODUCTION TO	2		HARE	3400	E-DE		COMPL		T				1	ı		-	JBSE1	DRMUL	Ī	
CE OF ARITHMETIC. THAT IS. A USER ORIENTED SYMBOL M PRESS IN A SINGLE LINGUISTIC STRUCTURE AN ARBITRARI THIS ASSIGNMENT-STATEMENT ABILITY IS COUPLED WITH DROCKERS TO GENERATE SPECIAL-PURPOSE PROGRAMS O ON RETRIEVAL (VINSONHALER). AND ANOTHER ANNOUNCEMEN VARIATIONS. INPUT AND OUTPUT EXAMPLES. AND SOME PO RES AS MIXED MODE EXPRESSIONS. GENERALIZED SUBSCRIP HE CONVERSATIONAL COMPILER SYSTEM (CCS). A GROUP OF E COC 3400 SYSTEM CURRENTLY INSTALLED AT NORTHWESTE PUTER WHICH COMPUTES TWO-AND THREE-STAGE LEAST SQUA AS. GOLDEN JAMES T HARE. INC AND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLA INTRODUCTION TO INTRODUCTION TO	ř		ב		TECT	င္ပ	ITING	000	WITH	CNOR	DPE				•	FR?	-	A TO	770.	RFOR
OF ARITHMETIC, THAT IS, A USER ORIENTED SYMBOL MESS IN A SINGLE LINGUISTIC STRUCTURE AN ARBITRARI MIS ASSIGNMENT-STATEMENT ABILITY IS COUPLED WITH PROGRAM-WRITING PROGRAMS, EXTENDING PROGRAMS OF RETRIEVAL (VINSONHALER), AND ANOTHER ANNOUNCEMEN ARIATIONS, INPUT AND OUTPUT EXAMPLES, AND SOME POSAS MIXED MODE EXPRESSIONS, GENERALIZED SUBSCRIPTOR WHICH COMPUTES TWO-AND THREE-STAGE LEAST SQUARE, INC. ND TOPOLOGICAL PREPROCESSING ARE COUPLED WITH CLARE, INC. BASIC INTRODUCTION TO TED SET OF ##PRIMITIVE## MACHINE LANGUAGE SUBROUT	7		LOIZ	Š	ZOZ	N-SI		S	_	X	ATUR	בור בור				X ·	ゴロス	N M X P		MANO
THMETIC, THAT IS, A USER ORIENTED SYMBOL MA SINGLE LINGUISTIC STRUCTURE AN ARBITRARI IGNMENT-STATEMENT ABILITY IS COUPLED WITH PROGRAM-WRITING PROGRAMS, EXTENDING ERS TO GENERATE SPECIAL-PURPOSE PROGRAMS OVAL (VINSONHALER), AND ANOTHER ANNOUNCEMEN OF INPUT AND DUTPUT EXAMPLES, AND SOME POWED MODE EXPRESSIONS, GENERALIZED SUBSCRIPSATIONAL COMPILER SYSTEM (CCS), A GROUP OF O SYSTEM CURRENTLY INSTALLED AT NORTHWESTE CH COMPUTES TWO-AND THREE-STAGE LEAST SQUADEN JAMES TO STED TROCESSING ARE COUPLED WITH CLASIC OF ##PRIMITIVE## MACHINE LANGUAGE SUBROUT OF ##PRIMITIVE## MACHINE LANGUAGE SUBROUT	1120	d N	0			ARE.		UTER	CDC	DO DO	ES A	YAMY	Z D 3	700	3 6 7		THIS	RESS		M C)
INGLE LINGUISTIC STRUCTURE AN ARBITRARI MENT-STATEMENT ABILITY IS COUPLED WITH OGRAM-WRITING PROGRAMS, EXTENDING TO GENERATE SPECIAL-PURPOSE PROGRAMS O (VINSONHALER), AND ANOTHER ANNOUNCEMEN INPUT AND OUTPUT EXAMPLES, AND SOME PO MODE EXPRESSIONS, GENERALIZED SUBSCRIP IONAL COMPILER SYSTEM (CCS), A GROUP OF YSTEM CURRENTLY INSTALLED AT NORTHWESTE COMPUTES TWO-AND THREE-STAGE LEAST SQUA JAMES T ICAL PREPROCESSING ARE COUPLED WITH CLA OUCTION TO	25	Z	BAS		TOPOL	N N	60 [[TIT	3400	NVER	SEL	AT TO	T X I							ARI.
THAT IS, A USER ORIENTED SYMBOL MELINGUISTIC STRUCTURE AN ARBITRARI STATEMENT ABILITY IS COUPLED WITH WRITING PROGRAMS, EXTENDING ENERATE SPECIAL-PURPOSE PROGRAMS OF CONHALER). AND ANOTHER ANNOUNCEMENT AND JUTPUT EXAMPLES, AND SOME POEXPRESSIONS, GENERALIZED SUBSCRIP COMPILER SYSTEM (CCS), A GROUP OF CURRENTLY INSTALLED AT NORTHWESTE STAGE LEAST SQUAST TO-AND THREE-STAGE LEAST TO-AND THREE-STAGE LEAST SQUAST TO-AND THREE-STAGE LEAST TO-AND THREE-STAGE LEAST TO-AND THREE-STAGE LEAST TO-AND THREE-STAGE LEAS	Ç	ROP	SIC	٠.	0100		MZ (SEC	SYS C	SATIC	KEO			7		DRO.	I GZI	N SII		TIME!
STIC STRUCTURE AN ARBITRARI NT ABILITY IS COUPLED WITH 9 PROGRAMS, EXTENDING SPECIAL-PURPOSE PROGRAMS O R), AND ANOTHER ANNOUNCEMEN UTPUT EXAMPLES, AND SOME PO SIONS, GENERALIZED SUBSCRIP ER SYSTEM (CCS), A GROUP OF TLY INSTALLED AT NORTHWESTE AND THREE-STAGE LEAST SQUA ESSING ARE COUPLED WITH CLA	T A A	CTIO		İ	À		AMES	MBUT	TEN	NAC.		-	VIZ	30		DAM			•	70.
STIC STRUCTURE AN ARBITRARI NT ABILITY IS COUPLED WITH 9 PROGRAMS, EXTENDING SPECIAL-PURPOSE PROGRAMS O R), AND ANOTHER ANNOUNCEMEN UTPUT EXAMPLES, AND SOME PO SIONS, GENERALIZED SUBSCRIP ER SYSTEM (CCS), A GROUP OF TLY INSTALLED AT NORTHWESTE AND THREE-STAGE LEAST SQUA ESSING ARE COUPLED WITH CLA	1 1 2 M	Z			REPR		4	-	CURR		EXPR	NO	CAI	Z		LDIT	76	LING	:	THAT
TRUCTURE AN ARBITRARILITY IS COUPLED WITH RAMS, EXTENDING AL-PURPOSE PROGRAMS OF ANOTHER ANNOUNCEMEN EXAMPLES, AND SOME PO GENERALIZED SUBSCRIPTEM (CCS), A GROUP OF STALLED AT NORTHWESTE HREE-STAGE LEAST SQUA ARE COUPLED WITH CLA	VE##			1	OCES			MO-A	ENTL	ILER	ESSI:	TUC	LER)	ie s	12	2	¥ 7 2 7	UIST		
	MAC							3 1	4 HZ	SYS	ONS.	PUT [A	PECI		D	ART	IC S	:	>
	I NA						1	BEE.	STALL	Z Z	GENE	EXAME	D NC	L-PC	777		114	TRUC!		
	LANG			9	9500			STAG	EO A	CCS)	RALI	LES	THER	MPCS	_ F > 1		70		•) 172
	UAGE			!					T NO	• >	ZED	PNO		E PR	4	7 (2)	2		1	750
	dens				1774			AST S	カイエエ	GROU	SUBS	SOM	CUNCI	CORAI		֓֞֞֜֜֜֞֜֜֜֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֜֜֜֓֓֡֓֜֜֜֓֓֡֓֡֓֡֓֡֡֡֜֜֡֓֡֓֡֓֡֡֡֡֓֜֡֡֡֡֓֜֡֡֡֡֡֓֜֡֡֡֡֡֓֡֡֡֡֓֜֡֡֡֡֓֜֝֡֡֡֡֡֓֜֝	7 (BR T T		n v W D
76000000000000000000000000000000000000	TOUT				2		1	AUG	STE	2	RIT	PO	NUN	S C		1		307	3	Z
	630 769	9		7	760	2	010	J (ب ا م	2	66	78	5 6	62	20	, q	A 4)	.	>

The decision as to what is or is not to be considered as a keyword is made in three ways. The computer can be instructed either to refer to a list of keywords prepared in advance by the researcher (KEY), or to a list that is not to be considered as keywords (stopword list), or can be instructed to index on every term in the file (NULL).

In the first case, the computer looks at every word contained in the level of information it is to search, compares it with its stored list of keywords, and selects matches for indexing. The process operates in a comparable way when a list of "stopwords" is used: the computer includes the word in the index only when it does not appear in the list. Sample stopwords are "a", "an", "of", "the", etc. but this list can be quite d' tinctive when applied to specific files. For example, a file of computer-related literature would have "computer" as a stopword since it is assumed that all entries would fall into this classification.

A KWIC index is also known as a "permuted" index, for an entry will appear as many times as the number of keywords it contains. The sample output in Figure 10 from the Midwest Journal file contained almost 200 articles, each of which was indexed an average of five times in a listing almost 1000 entries long.

When the KWIC (or AUTHOR) forms of output are selected, the only indication of the source of the entry is the reference code. This may, or may not, depending on the users' needs, require the generation of a separate "bibliographic" form of output in which the complete entry is listed in order of reference code. This is one form of KWOC output, with the reference code generated by the EDIT program used as the level of information (0) to be searched. This points up the fact that KWIC indexes are generally "double-entry" indexes; a KWOC index, on the other hand, is a "single-entry" index,

for it prints out (upon user option) as much of the complete entry as is desired for each appearance of a keyword.

Figure 13 reproduces a portion of output from a title index to the Vogelback Computing Center library. The index term is at the left of the page and each item indexed under that term is printed below. In this case, only author, title, and source information is printed. In other indexes to the same file, abstracts, coding categories, and shelf locations were printed.

Figure 14 shows an index to the same file where authors (level one information) were the designated search level. Another form of author index is a "short-form" index produced by the use of the *AUTHOR card. In this index, only the author's name and the reference code associated with that entry is listed (Figure 15).

The INDEX routines provide the user with the capability to choose which levels of information are to be searched and which levels are to be carried along as input to the PRINT routines (see p. 43). In addition, a STATISTICS option is available for counting and printing the total number of occurrences in a file of a key or stopword; the FREQUENCY option will print a listing of all words and their frequency within a given entry which will be used as indexing terms in KWOC output. This option is very useful when working with a new or large file; the frequency list can be printed and checked for desirability of indexing terms without printing the index itself. In this way, additional stopwords may be added to produce a final output pertinent to the user's needs.

SIMULATION

588

A10-70世 · @

GAFARIAN A V ET AL STATISTICAL APPROACH FOR VALIDATING SIMULATION MODELS BY COMPARISON WITH OPERATIONAL SYSTEM - ILLUSTRATED FOR TRAFFIC FLOW. SYSTEM DEVELOPMENT CORPORATION. SANTA MONICA, CALIFORNIA. FEBRUARY 1966. AD 632 478

GREENBERGER M
A NEW METHODOLOGY FOR COMPUTERS SIMULATION.
MASSACHUSETTS INSTITUTE OF TECHNOLOGY, CAMBRIDGE,
MASSACHUSETTS. 1964. AD 609 288

672

537

654

SMITH D L
MODELS AND DATA STRUCTURES FOR DIGITAL LOGIC SIMULATION.
MASSACHUSETTS INSTITUTE OF TECHNOLOGY. CAMBRIDGE
MASSACHUSETTS. AUGUST 1966. AD 637 192

ROME B K ROME S C HAYTHORN W W INFORMATION SYSTEMS SIMULATION AND MODELLING TECHNIQUES, SESSION 7, FIRST CONGRESS ON THE INFORMATION SYSTEM SCIENCES THE MITRE CORPORATION, BEDFORD, MASSACHUSETTS, DECEMBER 1963 AD 426 985

CONGER C R
THE SIMULATION AND EVALUATION OF INFORMATION RETRIEVAL
SYSTEMS
HRB - SINGER. INC.. SCIENCE PARK, STATE COLLEGE,
PENNSYLVANIA. APRIL 1965, AD 464 619

RAPHAEL R
SIR, A COMPUTER PROGRAM FOR SEMANTIC INFORMATION RETRIEVAL.
MASSACHUSETTS INSTITUTE OF TECHNOLOGY. CAMBRIDGE,
MASSACHUSETTS. JUNE 1964 AD 608 499

SNOBOL3
PORTE A
SNOBOL3 PRIMER.
THE MIT PRESS 1967. CAMBRIDGE. MASS.

SMOBOLA 631

ORISWOLD R E POAGE J F POLONSKY I P

PRELIMINARY REPORT ON THE SMOBOLA PROGRAMMING LANGUAGE.

INSTITUTE FOR DEFENSE ANALYSES, PRINCETON, NEW JERSEY.

MARCH 1 1968.

IVIE E L
IVIE E L
SEARCH PROCEDURES BASED ON MEASURES OF RELATEDNESS BETWEEN
DOCUMENTS.
MASSACHUSETTS INSTITUTE OF TECHNOLOGY, CAMBRIDGE,
MASSACHUSETTS. JUNE 1966. AD 636 275

JAHODA G
JAHODA G
ANALYSIS OF CASE HISTORIES OF PERSONAL-INDEX USE
FLORIDA STATE UNIVERSITY, TALLAHASSE, FLORIDA, JUL 1966.
AD 643 869

JANDA K
JANDA K
CUMULATIVE INDEX TO THE AMERICAN POLITICAL SCIENCE REVIEW.=
NORTHWESTERN UNIVERSITY PRESS, 1964.
COMPUTING CENTER LIBRARY.

JANDA K
DATA PROCESSING - APPLICATIONS TO POLITICAL RESEARCH.=
NORTHWESTERN UNIVERSITY PRESS. 1965.
COMPUTING CENTER LIBRARY.

JANDA K A MICROFILM AND COMPUTER SYSTEM FOR ANALYZING COMPARATIVE POLITICS LITERATURE. ICPP PROJECT, NORTHWESTERN UNIVERSITY, 1967. COMPUTING CENTER LIBRARY.

JANDA K (ED)
JANDA K (ED)
ADVANCES IN INFORMATION RETRIEVAL IN THE SOCIAL SCIENCES,
PART 1.
AMERICAN BEHAVIORAL SCIENTIST, JANUARY, 1967.

JANDA K (ED)
ADVANCES IN INFORMATION RETRIEVAL IN THE SOCIAL SCIENCES,
PART 2.
AMERICAN BEHAVIORAL SCIENTIST. FEBRUARY, 1967.

JOHNSON C H
JOHNSON C H
DATA PROCESSING.=
NATIONAL MACHINE ACCOUNTANTS ASSOCIATION.1959.
COMPUTING CENTER LIBRARY.

755	196	\$\$2 \$\$5	209	673	926)	6000	669	775	418	044	6 N N	100 F	77.	196			- -			100	1 S	10 4	617	715		0 () () () () () () () () () (+ • • • • • • • • • • • • • • • • • • •				625
SWEEN C	AFT T	TAYLOR R S ETAL	EITELMAN W		ALOMANO G G CA		MPSON F	g Z	7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	7 3 2 4 5 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5			FST	200	ES	7 1 1	10 VI	TAL W	유 2	REMA A L.	SONHALE	FOERS	A SOAH	LACE E			- L	HAL.	*	5	LZENBA	WER D J	ERNER	4
730	595 739	741	740	646		012	629	663	*00	* 6 4	# 64		764	104	648	050	762	414	033	488	523	522	6 09	586	567 776) (F)	475	686	657	424	672	620	755
RUBINOFF M Blbtworf M FT A	PUBLINGF H ETAL	AUOIX B D			E.	SALIZER U H		SALZMAN R M ET AL	:L A L	SANCHEZ A	SATTERLY G T JR	\mathbf{a}	SAYER J S	SCHEFFER F L	، ر		SCHOLLS L					I CLIS			SIMMONS R	フ -	O FEMALE O		SMALLWOOD R O ETAL	4 - C-740			SNOOFY & R	

Pigure 15. *AUTHOR (short-form) Index

INDEX Control Cards

All INDEX control cards are punched free-field, i.e., no column requirements. All instructions contained within brackets are optional. A period must be the last character on the *WORDS, *KWIC, and *KWOC cards. Each desired KWIC or KWOC index requires a set of INDEX and PRINT control cards (see sample job deck structure, p.46). Multiple indexes may be produced in one computer run by supplying multiple sets of INDEX and PRINT instruction cards, one set per printed output.

*MASTER = n

This instruction is used only when an existing (previously created and saved) file of information is to be used as input to the indexing routines, i.e., not as part of an EDIT and INDEX operation. n may be any unit from 1 to 5 and must be referenced on a system REQUEST card.

*INDEX (required)

To call in indexing routines *WORDS, name of index, CARDS $(n_1, n_2, ... n_m)$, [NULL], [STATISTICS].

> where name of index is user defined; can be any simple word or acronym meaningful to the user. This name must be repeated on the *KWIC or *KWOC card associated with this index. The WORDS card defines the levels of information to be searched (CARDS $(n_1, ..., n_m)$). The wordlist, if supplied, will be matched against terms contained only within these information levels.

The NULL option indicates that a word list is not supplied; therefore, all words will be used as indexing terms. STATISTICS will produce a frequency count of the number of times each word in the user-supplied word lists was encountered in the file.

Word list, either "key" or "stop", follows the *WORDS card. Words are punched free-field, separated by commas, with the last word ending in a period.

*KWIC, name, $\left[\text{KEY}\right]$, CARDS $(n_1, n_2...n_m)$, $\left[\text{NOWRAP}\right]$.

The *KWIC card indicates that output is to be in KWIC format. CARDS $(n_1...n_m)$ specify which levels of information are to be printed. "name" must be the same as specified on the *WORDS card. KEY indicates that a keyword list of indexing terms has been supplied and is to be used.

NOWRAP indicates output is nowrap format, i.e., keyword on left of page followed by context. If not specified, output will be "standard" NVIC, i.e., keyword running down vertical column of page, surrounded on both sides by context. (See Figure 10, p. 31)

*KWOC, name, $\left[\text{KEY}\right]$, CARDS $(n_1, n_2, ..., n_m)$, $\left[\text{FREQUENCY}\right]$.

Indicates output is to be in NVOC format.

"name" must be the same as that specified

on the WORDS card.

CALDS $(n_1, n_2...n_m)$ specifies which levels of information are to be carried into the PRINT program.

Note that if printing of a reference code is desired, the "O" level must be indicated.

KRY indicates that a user-supplied keyword list is to be used as index terms.

If not specified, a stopword or null list is assumed.

The FREQUENCY option will produce a list of the words that will be used for indexing and their frequency within each entry in the file. The frequency option does not accumulate a count over the entire file.

To produce a short-form alphabetized listing of authors (level one information) and the reference code associated with each entry. Output for single authors is triple column; corporate authors appear on a separate list in single column format. When using the *AUTHOR option, a *PRINT card must be included in the set even though print options are not available.

To return control to the executive overlay.

*AUTHOR

+500

PRINT Routines

Various output options are available to the user in conjunction with the indexing routines. A call to $ti \ni PRINT$ overlay is required for each printed index.

PRINT Control Cards

*PRINT

To call in the print routines.

OK.

Indicates default print conditions.

Output will be:

double column

no indentation

all levels of information will be

printed

reference code is not printed

line count per page = 60

spacing at top of page = 10

spacing on first page = 20

DOUBLE [COLUMN],

SINGLE [COLUMN],

CARDS (n_1, n_2, n_m) ,

To specify which levels of information

are to be printed

T) print reference code

To specify number of lines per page

To specify number of lines to be dropped

at top of page before printing

FEFERENCE [CODE],

[NUMBER OF] LINES = n,

[SPACING AT] TOP - n,

Abuitional at Beginning - n,

OUTPUT = u,

COPY = n,

INDENTATION

*END

To specify number of additional lines to be dropped on first page of printed index. This space may be used for title insertion.

where u must be either 2, 4 or 5;
u is a physical tape unit that output
will be written on. This option is
normally used when special printing is
desired. The output tape can be resubmitted at a later time for printing
using a COPY routine. A REQUEST card
must be supplied.

n is the number of times the output is
to be written on the user supplied
output tape. This is useful when
multiple copies of an index are desired.
Output entries are indented (within
entry).

To return control to main overlay.

<u>Print Control Card for KWIC Output</u>: (All words enclosed within brackets are optional) A period must follow the last specified option.

OK.

Indicates default print options desired.
Output will be:
lines per page = 60
spacing at top of page = 10
additional spacing on first page = 20

```
Options:
```

*END

```
[NUMBER OF] LINES = n,

[SPACING AT] TOP = n,

[ADDITIONAL AT] BEGINNING = n,

OUTPUT = u,

COPIES = n,
```

To return control to executive overlay.

When using the *AUTHOR option, the only PRINT cards needed are:

*PRINT

*END

TO PRODUCE AUTHOR AND TITLE INDEXES IN KWOC FORMAT FROM CARD INPUT:

(Note that although an EDIT of the input data must be performed before calling the INDEX routines, this file will not be saved for any subsequent processing since a disk scratch file is automatically assigned to the "master" file if a tape assignment using the REQUEST card is not supplied.)

VCC System Cards

VLORR, CHCM1235-9999, CM71200, T1000. LIBRARY (TRIAL3C) LGO. 7-8-9 End of Record

Create a file:

*EDIT
NEW MASTER - 1.
*DATA
*INSERT.
data cards
*END

Generate an unformatted author index

*INDEX
*WORDS, AUTHOR, CARDS (1).

user-supplied stopword list
*KWOC, AUTHOR, CARDS (1,2,3).
*END

Sort and print formatted author index

*PRINT OK. *END

Generate unformatted title index; print | *WCRI
list of words that
each entry will be indexed under, together | *END
with frequency of occurrence.

* INDEX

*WCRDS, TITLE, CARDS (2).

stopword list

*KWOC, TITLE, CARDS (1,2,3), FREQ.

Print in single column format title index, listing author and title only.

|*PRINT |SINGLE COLUMN, CARDS(1,2). |*END

6-7-8-9 End of Information

References

- 1. Aagaard, James S. and Roger J. Schaid, "Research on Advanced Telemetry Techniques: Bibliographic Data Processor", Aerial Measurements Laboratory, Northwestern University, Contract AF33(615)-1945, December 28, 1964.
- 2. Aagaard, James S., "BIDAP", American Behavioral Scientist, 10, February, 1967.
- 3. Borman, L., and Dillaman, D., "TRIAL for the CDC 3400", Vogelback Computing Center, Northwestern University, July 25, 1967.
- 4. Janda, Kenneth, "Keyword Indexes for the Behavioral Sciences", American Behavioral Scientist, 7, June, 1964.
- 5. Janda, K., and Milbrath, Lester W., "Computer Applications to Abstraction, Storage, and Recovery of Propositions from Political Science Literature", Paper presented at the 1964 Annual Meeting of the American Political Science Association.
- 6. Janda, K., (ed), <u>Cumulative Index to the American Political Science Review</u>, <u>Volumes 1-57, 1906-1963</u>, Evanston: Northwestern University Press, 1964.
- 7. Janda, K., <u>Data Processing: Applications to Political Research</u>, Evanston: Northwestern University Press, 1965.
- 8. Janda, K., "Information Retrieval: Applications to Bibliographies on International and Comparative Politics", Paper presented at the Computers and the Policy-Making Community Institute, Lawrence Radiation Laboratory, Livermore, California, April 4-15, 1966.
- 9. Janda, K., and Tetzlaff, William H., "TRIAL: A Computer Technique for Retrieving Information from Abstracts of Literature", <u>Behavioral Science</u>, 11, November, 1966.
- Janda, K., and Rader, Gary, "Selective Dissemination of Information: A Progress Report from Northwestern University", <u>American Behavioral Scientist</u>, 10, January, 1967.
- 11. Janda, K., <u>Information Retrieval: Applications to Political Science</u>, Indianapolis and New York: The Bobbs-Merrill Company, Inc., 1968.
- 12. Tetzlaff, William H., "TRIAL: Technique for Retrieving Information from Abstracts of Literature a Program for the IBM 709/90/94", Paper presented at the SHARE XXVI meeting, Applied Management Sciences Project Committee, San Diego, California, February 28-March 4, 1966.

TRIAL Internal Record Format (to be used when <u>altering</u> lines of an existing entry (ALTER))

Col. 1-60 New line of input data

Col. 61 Level number

Col.62-66 Line number to be altered. EDIT LIST must be referenced.

Col.67-68 Repeating group identifier, if any. EDIT LIST must be referenced.

Col.69-8. Reference information as punched in col. 61-72 of original data.

13. ABSTRACT

TRIAL is an information processing system that will perform editing, indexing, and retrieval of textual and certain types of numeric information. The system permits the creation and maintenance of a master file, indexing on works decignated as key words or, alternatively, on every word in the text (excluding common terms that are more supplied as step words), and computer retrieval and printent of entries that satisfy a user course common. One or may combination of these features can be achieved in one computer run with proper control cards. TRIAL was originally written in machine language for the IEM 709 in 1964, and was rewritten for the CDC 3600 in 1966. Details concerning input date properation, creation of a master file, and search and retrieval methods are reported. TRIAL has been associately used ince selective disconnation of information system. It is especially adaptable to large files of bibliographic date from which selective bibliographics or various forms of indexes are decired.

Selectified

Documby Classification	LINK	•	LIME	8	LINE	× 2
KEY KORDS	ROLE	WT	ROLE	WT	ROLE	•
			i			1
Laforactina storage and retrieval						l
garbara: bistram						Ì
Backward is a famous an						İ
Programming Lenguage						
Large files	1		j		Ì	
RATES A					ì	1
Relaxed language date		l			1	
Tent medipaletien Costal celemos deta	ļ	}				1
iosisi eclasso deta			1			1
In aday		!	ì			1
	1				1	
	i	l	1	1	1	İ
	Į.	1	1	l	1	
		1	Ì	l	l	[
	1		1	ļ		
	l	1	1	j		1
. The second of the second of	1	1	1		1	
	1			}		ļ .
	1	ļ	1	1		1
	1	1	1	1	1	
	1	1	1	1		
	1	l	1			
	ř	j	[1	•	1
		1	1	1	İ	Į
	1					
	}	1	1	1	1	1
	1			1	j	1
	!					Ì
		1			1	ĺ
	ĺ		1	į	1	
	1	1	1	1	1	į
	1			1		į
	1	1	i	1	1	1
	1		Ī	Į.	i	i
	1	i			į	
]			1	•
	1	į	1]		ĺ
		į	Į			
	1		1			ļ
	Ì	ļ			Ì	
			ĺ		į	
	į	1	1		ĺ	4
	1	[į		
	1	1	ĺ			
		1				
		Į		-		
		1			4	
	1	į	Ì			
	Ì	; •	i			
	Ĭ		1	1	•	
	-			Ē.		
	Ì		-			
		1		Į.		
		1	1	ži.		
	į	i	?	i	1 1	

Security Changes acree